

VIC MAC CORPORATION

An ISO 9001:2015 Certified Organization
Plot 265, Phase VI, Udyog Vihar, Gurugram, Haryana 122001, India

BULLET PROOF SHIELD

Ballistic Protection Structures

PRODUCT VIEWS



PRODUCT OVERVIEW

The VIC MAC Bullet-Proof Shield is a single-man mobile ballistic protection system designed for armed forces, police and paramilitary deployment. The common documented configuration uses a single 6.5 mm certified ballistic-steel plate measuring 40 x 48.5 inches, with an integrated ballistic-glass view port, firing port with sliding ballistic shutter, A-frame support and three lockable castor wheels. The documented configuration is intended for NIJ Level III / III+ protection against 7.62 x 51 mm SLR and 7.62 x 39 mm AK-47 threats, subject to the applicable certified plate and test report.

KEY FEATURES

- Single-piece 6.5 mm ballistic-steel plate with no joints.
- Common plate size: 40 x 48.5 in (approx. 1016 x 1232 mm).
- Ballistic-glass view port positioned above the firing port.
- 175 x 125 mm firing port with sliding ballistic-steel shutter.
- A-frame steel support for freestanding deployment.
- Three lockable castor wheels - one front centre and one at each rear side.
- Two rear-mounted carry handles for manual repositioning.
- Replacement firing-port shutters and customer-specified colour / finish available.

TECHNICAL SPECIFICATIONS

VIC MAC CORPORATION

An ISO 9001:2015 Certified Organization
Plot 265, Phase VI, Udyog Vihar, Gurugram, Haryana 122001, India

Parameter	Common / Indicative Specification
Protection Level	NIJ Level III / III+ - common documented configuration
Common Threats	7.62 x 51 mm SLR / 7.62 x 39 mm AK-47, as applicable to certified plate
Shot Spacing	Min. 20 mm between shots Min. 30 mm from plate edges
Plate Size	40 x 48.5 in (approx. 1016 x 1232 mm)
Plate Thickness	6.5 mm $\pm$ 0.5 mm
Total Weight	70 kg $\pm$ 5 kg
Plate Construction	Single plate - no joints
BP Glass View Port	Ballistic-glass view port positioned above firing port; documented against AK-47 / 7.62 SLR threat at 10 m
Firing Port	175 x 125 mm ($\pm$ 5 mm) with sliding ballistic-steel shutter
Support Stand	A-frame steel stand - freestanding deployment
Mobility	3 castor wheels with locking system - 1 front centre + 1 each rear side
Carry Handles	2 rear-mounted handles for manual repositioning
Shutter Replacement	Replacement sliding shutter available if damaged
Colour / Finish	As per customer requirement
Material / Testing	Test certificate available; ballistic steel documented through TBRL Chandigarh (MoD) / Gujarat NFSU

APPLICATIONS

- Armed forces
- Police and paramilitary
- Single-operator ballistic protection deployments
- Static or repositionable security positions requiring frontal ballistic cover

COMMERCIAL AND TECHNICAL TERMS

Specifications shown are common or indicative configurations. Final dimensions, protection level, materials, testing, warranty, delivery schedule, price, GST and freight are governed by the approved quotation, purchase order and applicable test certificate.

Price on request. Contact VIC MAC Corporation with the required quantity and configuration.